

~~OPTICAL IRRADIATION DEVICE~~

[illegible]

It has already been proposed to use light-emitting diodes LEDs in a hand held device to produce a focused beam of light to cure dental materials. Blue light at a peak wavelength of about 470nm is used to harden dental polymers which contain camphoroquinone as the photoinitiator in a methacrylate polymerisation process. However, there is a problem in producing a sufficient level of irradiance even with a clustered array of LEDs, to cure the known dental polymers in the recommended time. At the lower levels of irradiance available generally below 300mW/sq.cm, longer curing times have to be allowed, which reduces the efficiency of the dental treatment delivered.

An object of the present invention is to provide an optical irradiation device that employs LEDs, and thereby has the benefits of compactness, portability, ruggedness and long

According to a first aspect of the invention, LEDs are clustered in an irradiation device by forming shaped facets on adjacent LEDs which allow them to adjoin more closely than they would otherwise with conventional spherical outer surfaces as manufactured currently.

According to a second aspect, the invention consists in a tapered light guide for an optical irradiation device, which light guide is tapered from its input end to its output end and has an intermediate region of minimum diameter in which a bend is formed.

According to a third aspect, the invention consists in an optical irradiation device employing LEDs and incorporating a heat pipe to cool the LEDs.

According to a fourth aspect, the invention consists in a heat pipe comprising inner and outer walls that extend longitudinally from one end of the heat pipe to the other and define an annular space therebetween containing a material that serves to absorb heat by a phase change, the annular space being divided by internal walls into a plurality of fluid flow channels that extend longitudinally between said

ends, some of said channels being adapted to conduct the liquid/vapour phase of said material from the hot end of the heat pipe to the cold end, and other channels being adapted to return said liquid phase from the cold end of the pipe to the hot end.

According to a fifth aspect, the invention consists in an irradiation device employing LEDs and a tapered light guide to collect radiation emitted by the LEDs and deliver this to an output beam, wherein two or more tapered light guides are arranged in series so that successive guides receive radiation from preceding guides, and a group of LEDs is provided at the input end of each guide, each successive guide preferably being provided with a ring of LEDs around the output end of the preceding guide.

The first aspect of the invention means that LEDs occupy more of the available space, and a fixed number produce a higher radiant intensity. Thus, smaller numbers of LEDs can be used to produce a desired level of irradiance, which in turn reduces the power required to drive the device and the heat generated by it. Furthermore, the device can be made more compact. Packing of the LEDs in this way may involve a slight reduction in the output of each LED, but the more effective packing density produces an overall increase in irradiance.

Typically, a central LED might have a polygonal outer surface, and a first ring of LEDs would be arranged around it, each with a flat face to abut a corresponding face of the central LED and possibly each having a pair of radiating side faces which abut adjacent LEDs in the first ring. Furthermore, a second or more rings of LEDs could be arranged concentrically with the first ring, each with respective adjacent flat side faces abutting one another and possibly with inwardly diverted faces abutting respective outwardly directed faces of the LEDs of the inner ring. Alternatively, a single ring or two or more concentric rings of LEDs could be used without a central LED.

DESCRIPTION OF THE DRAWINGS

The invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 is a schematic cross-section through a first embodiment of the invention comprising a cluster of hexagonal section LEDs;

Figure 2 is a schematic cross-section through a second embodiment of the invention comprising a cluster of an inner group of LEDs and an outer ring of LEDs;

Figure 4 is a schematic side elevation of a fourth embodiment of the invention;

Figure 5 is a schematic longitudinal section through a fifth embodiment of the invention;

Figure 6 is a schematic longitudinal section through a sixth embodiment of the invention;

Figure 7 is a schematic cross-section through a bundle of light guide fibres with modified sections;

Figure 8 is a schematic side elevation of a tapered light-guide according to another embodiment of the invention; and

Figure 9 is a schematic cross-section through a heat pipe according to the invention.

In a typical optical irradiation device according to the invention, a plurality of LEDs are clustered together so as to

direct emitted radiation into a single beam. A cluster of LEDs 43 is shown in side view in Figure 4, and in plan view or cross-section in Figures 1 to 3. Each LED comprises a light-emitting semiconductor Pn junction (not shown) which is encapsulated in an outer plastics envelope, the profile of which is shown in the drawings. The sides of the LED envelope are shaped to allow the LEDs to be clustered together more closely at their bases, thereby increasing the ratio of occupied to unoccupied space in the cluster of LEDs. The tips of the LEDs are substantially spherical and transmit the radiation to form the beam.

In the embodiment of the invention illustrated in Figure 1 the outer envelope of the LEDs is hexagonal in cross-section, and the LEDs are clustered in the manner of a honeycomb as shown, with adjacent facets abutting one another.

In the second embodiment of the invention illustrated in Figure 2, a central LED 21 of hexagonal cross-section has facets which abut adjacent facets of six LEDs 22 in a first ring of LEDs with radially extending side facets that allow adjacent LEDs in the ring to abut one another. A second ring of LEDs 23 is arranged around the first ring of LEDs, and these LEDs 23 have radially extending side facets that allow adjacent LEDs in the ring to abut one another.

In a third embodiment of the invention shown in Figure 3, an inner ring of nine LEDs 31 in a first ring is contained within a second ring of LEDs 32, and radially extending side facets of the LEDs in both rings allow adjacent LEDs in each ring to abut one another.

Both the second embodiment of Figure 2 and the third embodiment of Figure 3 may be modified by the addition of one or more further concentric rings of LEDs. Also, the circumferential facets of the LEDs of each ring may be shaped to abut similarly shaped circumferential facets of the adjacent ring of LEDs.

In yet another embodiment, the central group of LEDs 21,22 of Figure 2 may be replaced by the same number of LEDs in a honeycomb cluster. Yet another embodiment may consist of the single ring of LEDs 31 shown in Figure 3. It will be appreciated in all three illustrated embodiments, the LEDs are mounted in a substantially flat plane.

In modifying the conventional optical sphere shape of the outer plastics envelope of a LED care has to be taken to preserve as much as possible of the focusing effect of the envelope to maximise the total irradiance. However, because the envelope of existing LEDs have a tapered shape to assist their removal from the mould during manufacture, the shaped

side facets can be formed around the broader base of the LED to change its cross-section, for example to become hexagonal, but with these facets having a reducing effect on the shape of the envelope towards its tip where the focusing effect of the envelope is concentrated. Thus the invention can employ existing LEDs and modify their shape in a secondary manufacturing process, for example, using jigs, or the invention can employ LEDs which have been specially manufactured with the required outer envelope shape to accommodate better clustering.

The shaped facets of the LEDs may be polished to enhance reflection and help reduce any loss of optical powers. Additionally, a reflective metallic film may be applied to the shaped facets to further enhance reflection.

The LEDs may also incorporate a microlens or microlens array to aid collimation of the beam.

50
42
The electrical connections of the LEDs, known as lead frames 44, are connected to respective positive and negative power terminals or bus bars 42. Preferably, these terminals are adapted to serve the dual function of heat sinks to help remove heat generated by the LEDs 43. Thus, the terminals are formed of a good thermal conductor such as copper, and are located in the optimum location relative to the LEDs and the

external surfaces of the device. In one particular embodiment most suited to the LED array of Figure 3, the terminals 42 take the form of two concentric rings, each lying adjacent to the bases of one ring of LEDs 31 or 32. Preferably, the negative terminal is the outer one because the negative lead frames 44 of the LEDs generally get hotter than the positive lead frames 44.

The typical optical irradiation device according to the invention also preferably incorporates a tapered light guide, shown as guide 41 in Figure 4, to collect light emitted by the LEDs and deliver this as an output beam. It is known to use light guides with adiabatic optical tapers in optical irradiation devices so that there is total internal reflection of the light as it is conducted from the light source to the output. However, an advantage of the invention is that the more compact cross-section of the LED cluster means that the diameter at the input end of the light guide can be smaller, and thus a smaller angle of adiabatic taper (i.e. the ratio of the diameter of the input end to the output end of the light guide) can be provided in the light guide with the consequent more efficient transmission of radiant energy and increased illuminance. This improvement is most marked compared with a conventional approach of simply increasing the numbers of LEDs in a cluster at ever increasing diameters with decreasing

$$\text{Sub } a^3$$

12345678910111213141516171819202122232425262728293031323334353637383940414243444546474849505152535455565758596061626364656667686970717273747576777879808182838485868788899091929394959697989910010110210310410510610710810911011111211311411511611711811912012112212312412512612712812913013113213313413513613713813914014114214314414514614714814915015115215315415515615715815916016116216316416516616716816917017117217317417517617717817918018118218318418518618718818919019119219319419519619719819920020120220320420520620720820921021121221321421521621721821922022122222322422522622722822923023123223323423523623723823924024124224324424524624724824925025125225325425525625725825926026126226326426526626726826927027127227327427527627727827928028128228328428528628728828929029129229329429529629729829930030130230330430530630730830931031131231331431531631731831932032132232332432532632732832933033133233333433533633733833934034134234334434534634734834935035135235335435535635735835936036136236336436536636736836937037137237337437537637737837938038138238338438538638738838939039139239339439539639739839940040140240340440540640740840941041141241341441541641741841942042142242342442542642742842943043143243343443543643743843944044144244344444544644744844945045145245345445545645745845946046146246346446546646746846947047147247347447547647747847948048148248348448548648748848949049149249349449549649749849950050150250350450550650750850951051151251351451551651751851952052152252352452552652752852953053153253353453553653753853954054154254354454554654754854955055155255355455555655755855956056156256356456556656756856957057157257357457557657757857958058158258358458558658758858959059159259359459559659759859960060160260360460560660760860961061161261361461561661761861962062162262362462562662762862963063163263363463563663763863964064164264364464564664764864965065165265365465565665765865966066166266366466566666766866967067167267367467567667767867968068168268368468568668768868969069169269369469569669769869970070170270370470570670770870971071171271371471571671771871972072172272372472572672772872973073173273373473573673773873974074174274374474574674774874975075175275375475575675775875976076176276376476576676776876977077177277377477577677777877978078178278378478578678778878979079179279379479579679779879980080180280380480580680780880981081181281381481581681781881982082182282382482582682782882983083183283383483583683783883984084184284384484584684784884985085185285385485585685785885986086186286386486586686786886987087187287387487587687787887988088188288388488588688788888989089189289389489589689789889990090190290390490590690790890991091191291391491591691791891992092192292392492592692792892993093193293393493593693793893994094194294394494594694794894995095195295395495595695795895996096196296396496596696796896997097197297397497597697797897998098198298398498598698798898999099199299399499599699799899910001001100210031004100510061007100810091010101110121013101410151016101710181019102010211022102310241025102610271028102910301031103210331034103510361037103810391040104110421043104410451046104710481049105010511052105310541055105610571058105910601061106210631064106510661067106810691070107110721073107410751076107710781079108010811082108310841085108610871088108910901091109210931094109510961097109810991100110111021103110411051106110711081109111011111112111311141115111611171118111911201121112211231124112511261127112811291130113111321133113411351136113711381139114011411142114311441145114611471148114911501151115211531154115511561157115811591160116111621163116411651166116711681169117011711172117311741175117611771178117911801181118211831184118511861187118811891190119111921193119411951196119711981199120012011202120312041205120612071208120912101211121212131214121512161217121812191220122112221223122412251226122712281229123012311232123312341235123612371238123912401241124212431244124512461247124812491250125112521253125412551256125712581259126012611262126312641265126612671268126912701271127212731274127512761277127812791280128112821283128412851286128712881289129012911292129312941295129612971298129913

An alternative light guide is illustrated in Figure 8 in which the bend in the light guide 41 is provided at a waisted section 46 in its length which reduces to a minimum diameter

sub
b2

82

~~together.~~ A guide of this design is manufactured by MicroQuartz Sciences Inc. of Phoenix, Arizona, USA. In this way, the diameter of each fibre is smaller than a single homogeneous guide rod so that they allow greater light transmission on bending around the same bend radius, but also the packing fraction is also greatly reduced over conventional

fibre guides, resulting in a greater than 90% core availability at the input end of the guide.

In another embodiment of the invention, a graded-index optical light guide is used. A graded-index light guide has no sudden interface between the cladding and the core. Instead, the refractive index varies either radially or axially. In one embodiment, the gradient of the refractive index of the light guide varies both radially and axially so that the light energy is favourably manipulated. A guide that uses a stepped index could also be used with the same axial and radial variation in refractive index. In this way, the numeric aperture can be varied at either end of the guide to achieve the desired transmission.

In other embodiments of the invention, instead of providing a single tapered light guide, each LED or groups of LEDs could be provided with its own light guide fibre incorporating an adiabatic optical taper, and the output ends of these fibres could be collected together to form a single output beam. The input end of the fibre would be moulded optically to the adjacent LED or group of LEDs for efficient transmission of radiation. In this way, the diodes can be spaced more widely to dissipate unwanted heat. In yet another embodiment of the invention, each LED could be adjusted so that its outer envelope is extended into a fibre light guide which

The light guide or light guides used according to the invention may be formed with an outer metallic coating to improve its performance.

It will be appreciated that the irradiance of the device according to the invention can be varied by varying the input power, number of LEDs, or by varying the adiabatic taper of the light guide.

Cooling of the LED cluster can be aided according to another feature of the invention by arranging that the electrical connections of each LED are thermally connected to one or more heat pipes. Conventional LED irradiation devices usually include a heat sink to conduct away the heat from the LED chips. Heat sinks are generally slow and inefficient in conducting heat away from a heat source compared with heat pipes. Heat pipes conduct heat away rapidly by using the latent heat of a substance, such as water, which is vaporised by the heat from the source. The vapour moves at high speed to the cooler end of the heat pipe and condenses. Heat pipes

Sub
a₄

[illegible]

Because of the greater cooling ability of heat pipes, they allow the LEDs to be driven in such a manner as to produce more radiation, and thus allows a more powerful device to be manufactured.

Sub
a₅

sub
a⁶

06393

The wavelengths of the LED used will depend upon the applications of the device. A LED emitting blue light with a peak wavelength of about 470nm is used to harden dental polymers, but a LED emitting red light may be useful for photodynamic therapy, for example, cancer therapy.

The wavelength of light emitted by the LEDs may be modified in a light guide by doping the material from which it is composed with fluorescent material. This can serve to lengthen the wavelength of the emitted light so as to suit the particular application.

The choice of LED is also important in terms of its construction, diameter, irradiance and light angular spread pattern. From a range of known LEDs the best available choice has been determined as that with a 3mm diameter rather than a 5mm diameter and an angular spread of 30 degrees rather than 15 or 45 degrees. Nichia is the manufacturer of these LEDs.

It will be appreciated that the term "light-emitting diode-LED" as used herein also includes laser diodes.

LEDs in the devices according to the invention may be operated in a pulsed mode or modulated mode to vary the output radiation intensity to suit the application, and multiple clusters of LEDs, such as in the embodiment of Figure 6, may each be generated in a different mode.

The power supply for the LEDs of the device according to the invention could be mains power, battery power, capacitor,

In one embodiment, a capacitor or supercapacitor could be used to power the array having advantages over conventional rechargeable sources such as batteries. Capacitors can be virtually instantaneously recharged between one or more curing cycles of operation when the unit is connected to a power source.

The power supply for the device may be re-chargeable, and may be designed to make automatic electrical contact with the charging means of a base unit when engaged with the latter in the manner of a cordless telephone handset.